

SWA Cable Gland Matching Chart

ELAND RANGE

FCG-BW: for indoor use

FCG-CW: for outdoor use

DIMENSIONS

NOMINAL CROSS SECTIONAL AREA mm ²		NO. OF CORES												
		1	2	3	3.5	4	5	7	10	12	19	27	37	48
1.5	-	-	20S	20S	-	20S	20S	20S	20	20	25S	25	32	32
2.5	-	-	20S	20S	-	20S	20	20	25S	25S	25	32	32	40
4	-	-	20S	20	-	20	20	25S	32	32	32	40	-	-
6	-	-	20	20	-	20	Size: BW-20L Glands manufactured to BS 6121 Pt 1. For use with SWA and AWA cables. Warning: This chart is for guidance only – actual cable dimensions should be considered before making final selection as these may vary due to manufacturing tolerances.							
10	-	-	20	20	-	25S								
16	-	-	25S	25	-	25								
25	16	-	25S	25	32	32								
35	16	-	25	32	32	32								
50	25	25S	32	32	40	40								
70	35	25S	32	40	40	40								
95	50	25	40	40	50S	50S								
120	70	32	40	50S	50	50								
150	70	32	50S	50	50	63S								
185	95	32	50	50	63S	63								
240	120	40	50	63S	63	75S								
300	150	40	63S	63	75S	75								
300	185	-	-	-	75	-								
400	185	50S	63	75S	90S	90S								