



# N2XS(FL)H 12/20 (24)kV Cable



Eland Product Group: A9X

## APPLICATION

Medium voltage power cables for distribution networks and generation units. LSZH outer sheathing makes the cable suitable for internal installation as well as directly in ground, outdoors, and in cable ducts. UV Resistant.

## CHARACTERISTICS

**Voltage Rating** U<sub>0</sub>/U (Um)  
12/20 (24)kV

**Test Voltage**  
42kV AC 50Hz (5 mins)

**Temperature Rating**  
-20°C to +60°C  
Permissible Conductor Operating Temperature: +90°C  
Permissible Short Circuit Temperature up to 5 sec: 250°C

**Minimum Bending Radius**  
15 x overall diameter

## CONSTRUCTION

**Conductor**  
Class 2 Stranded Copper

**Conductor Screen**  
Semi-conductive material

**Insulation**  
XLPE (Cross-Linked Polyethylene)

**Insulation Screen**  
Semi-conductive material (bonded)

**Longitudinal Waterblocking**  
Semi-conductive swellable tape

**Screen**  
Copper wires and copper tape

**Longitudinal Waterblocking**  
Swellable Tapes

**Radial Waterblocking**  
Al/PET (Aluminium/Polyester) tape tightly bonded to sheath

**Outer Sheath**  
LSZH (Low Smoke Zero Halogen)

**Sheath Colour**  
● Red ● Black

## STANDARDS

IEC 60502-2, IEC 60228,  
Low Smoke Zero Halogen: IEC 60754-1/2, IEC 61034-2  
Flame Retardant: IEC 60332-3-24 CatC, IEC 60332-1-2  
UV Resistant: ISO 4892-3  
Abrasion and Tear Resistant: EN 60229-4.1  
Impact rated to: AG2 EN 60364-5.51

## THE CABLE LAB<sup>®</sup>

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



## SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: [www.elandcables.com/company/about-us/esg-sustainability](http://www.elandcables.com/company/about-us/esg-sustainability)



## REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/863/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup>.





## DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>		NOMINAL CONDUCTOR DIAMETER mm	NUMBER WIRES CONDUCTOR mm	NOM. THICKNESS SEMI-CON. LAYER		NOMINAL INSULATION THICKNESS mm	MINIMUM INSULATION THICKNESS mm	NOMINAL DIAMETER OVER INSULATION mm
		Conductor	Screen			INNER mm	OUTER mm			
A9XHL20KV1050RDC	1	50	16	8.10	10 x 2.62	0.50	0.40	5.50	4.85	20.3
A9XHL20KV1070RDC	1	70	16	9.70	14 x 2.62	0.50	0.40	5.50	4.85	21.9
A9XHL20KV1095RDC	1	95	16	11.4	19 x 2.62	0.50	0.40	5.50	4.85	23.6
A9XHL20KV1120RDC	1	120	16	12.7	19 x 2.97	0.50	0.40	5.50	4.85	24.9
A9XHL20KV1150RDC	1	150	25	14.5	19 x 3.20	0.50	0.40	5.50	4.85	26.7
A9XHL20KV1185RDC	1	185	25	15.9	27 x 2.62	0.50	0.40	5.50	4.85	28.1
A9XHL20KV1240RDC	1	240	25	18.6	48 x 2.62	0.50	0.40	5.50	4.85	30.8
A9XHL20KV1300RDC	1	300	25	20.7	61 x 2.62	0.50	0.40	5.50	4.85	32.9
A9XHL20KV1400RDC	1	400	35	23.5	61 x 2.97	0.50	0.40	5.50	4.85	35.7
A9XHL20KV1500RDC	1	500	35	26.5	61 x 3.29	0.50	0.40	5.50	4.85	38.7
A9XHL20KV1630RDC	1	630	35	30.2	61 x 3.80	0.50	0.40	5.50	4.85	42.9

NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	NUMBER WIRES SCREEN mm	DIAMETER TAPE SCREEN mm	NOMINAL SHEATH THICKNESS mm	MINIMUM SHEATH THICKNESS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km	MAXIMUM SIDEWALL PRESSURE N/cm <sup>2</sup>	MAXIMUM PULLING TENSION N
50	44 x 0.66	1x0.1x10	1.80	1.24	27	1100	475	2500
70	44 x 0.66	1x0.1x10	1.90	1.32	29	1400	603	3500
95	44 x 0.66	1x0.1x10	1.90	1.32	31	1600	747	4750
120	44 x 0.66	1x0.1x10	2.00	1.40	32	1900	895	6000
150	71 x 0.66	1x0.1x10	2.00	1.40	34	2250	1031	7500
185	71 x 0.66	1x0.1x10	2.10	1.48	35	2500	1188	9250
240	71 x 0.66	1x0.1x10	2.10	1.48	38	3250	1389	12000
300	71 x 0.66	1x0.1x10	2.20	1.56	40	4000	1621	15000
400	60 x 0.85	1x0.1x15	2.30	1.64	44	5000	1975	20000
500	60 x 0.85	1x0.1x15	2.40	1.72	47	6000	2268	25000
630	60 x 0.85	1x0.1x15	2.50	1.80	51	7250	2555	31500



## ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	CONDUCTOR DC RESISTANCE AT 20°C ohms/km	CONDUCTOR DC RESISTANCE AT 75°C ohms/km	CONDUCTOR AC RESISTANCE BY MAX TEMP ohms/km	CURRENT CARRYING CAPACITY ( A )		REACTANCE ohms/km	CHARGING ADMITTANCE A/km	CAPACITANCE uF/km	S.C.C CONDUCTOR 1SEC kA	S.C.C SCREEN 1SEC kA	CONDUCTOR LOSSES IN THE GROUND kW/km
				In Ground 20°C	In Air 30°C						
50	0.387	0.801	0.497	250	279	0.19	0.40	0.15	7.15	3.2	31.1
70	0.268	0.555	0.344	304	347	0.19	0.38	0.17	10.1	3.2	31.8
95	0.193	0.399	0.248	361	420	0.18	0.36	0.19	13.59	3.2	32.3
120	0.153	0.316	0.196	407	483	0.18	0.35	0.20	17.16	3.2	32.5
150	0.124	0.160	0.256	445	540	0.17	0.33	0.22	21.45	5.0	31.7
185	0.0991	0.205	0.128	498	617	0.17	0.32	0.24	26.46	5.0	31.7
240	0.0754	0.156	0.0980	569	718	0.16	0.31	0.27	34.32	5.0	31.7
300	0.0601	0.124	0.0800	633	813	0.16	0.30	0.29	42.90	5.0	32.1
400	0.0470	0.0974	0.0640	686	904	0.16	0.29	0.32	57.20	7.1	30.1
500	0.0366	0.0758	0.0510	756	1011	0.15	0.28	0.36	71.50	7.1	29.1
630	0.0283	0.0420	0.0586	850	1030	0.15	0.28	0.40	90.09	7.1	30.3

Derating factor (ground): 1 (Soil thermal resistivity: 1km/W, Depth 0.8m, Flat formation - touching)

Derating factor (air): 1 (Flat formation - touching)

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.