



2192Y / H03VVH2-F EN 50525-2-11 Flexible Cable



Eland Product Group: A3Y

APPLICATION

Light duty cable for use in domestic premises, kitchens and offices. For use as pendant light drops and light supply leads.

CHARACTERISTICS

Voltage Rating U_o/U
300/300V

Temperature Rating
Flexed: +5°C to +70°C

Minimum Bending Radius
Flexed: 8 x overall diameter

CONSTRUCTION

Conductor
Class 5 flexible copper conductor

Insulation
PVC (Polyvinyl Chloride)

Sheath
PVC (Polyvinyl Chloride)

Core Identification
● Blue ● Brown

Sheath Colour
○ White ● Black

STANDARDS

EN 50525-2-11, EN 60228

Flame Retardant according to IEC/EN 60332-1-2

THE CABLE LAB®

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab®.





DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL THICKNESS OF INSULATION mm	NOMINAL THICKNESS OF SHEATH mm	NOMINAL OVERALL DIAMETER H x W mm	NOMINAL WEIGHT kg/km
A3Y020050* FLAT	2	0.5	0.5	0.6	3.35 x 5	30
A3Y020075* FLAT	2	0.75	0.5	0.6	3.5 x 5.5	37

* Designates the sheath colour. For each Eland Cables part number replace with the colour code as listed below . e.g. A3Y020050BK FLAT = 0.5mm² Black

COLOUR CODES

COLOUR	White	Black
CODE	WH	BK

CONDUCTORS

Class 5 Flexible Copper Conductors for Single Core and Multi-Core Cables

NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM DIAMETER OF WIRES IN CONDUCTOR mm	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km	
		Plain Wires	Metal-Coated Wires
0.5	0.21	39	40.1
0.75	0.21	26	36.7

The above table is in accordance with BS EN 60228 (previously BS 6360)

ELECTRICAL CHARACTERISTICS

Current Carrying Capacity and Mass Supportable

NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		MAXIMUM MASS SUPPORTABLE BY TWIN FLEXIBLE CORD (See Regulations 522.7.2 and 559.6.1.5 of the 17th Edition of IEE Wiring Regulations) kg
	Single-Phase AC	Three-Phase AC	
0.5	3	3	2
0.75	6	6	3

The above table is in accordance with Table 4F3A of the 18th Edition of IEE Wiring Regulations BS7671 and IEC 60364-5-52.

VOLTAGE DROP

NOMINAL CROSS SECTIONAL AREA mm ²	DC OR SINGLE-PHASE AC mV/A/m	THREE-PHASE AC mV/A/m
0.5	93	80
0.75	62	54

Conductor operating temperature: 60°C

The above table is in accordance with Table 4F3B of the 18th Edition of IEE Wiring Regulations BS7671 and IEC 60364-5-52.

DE-RATING FACTORS

60°C Thermoplastic or Thermosetting Insulated Cords

AIR TEMPERATURE	35°C	40°C	45°C	50°C	55°C
DE-RATING FACTOR	0.91	0.82	0.71	0.58	0.41

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.