

ELAND[®]
CABLES

Veriflex[®] DeviceNet Thin LSZH Cable



APPLICATION

Veriflex[®] DeviceNet cable suitable for fixed and occasional flexing indoor applications in CAN technologies. LSZH (Low Smoke Zero Halogen) sheath. The accurate construction and the high shielding efficiency guarantee excellent transmissive performances in environments particularly polluted by electromagnetic interferences. Connects industrial devices, motor starters and PLCs.

CHARACTERISTICS

Voltage Rating
125V

Temperature Rating
Fixed: -20°C to +80°C
Flexed: -5°C to +50°C

Minimum Bending Radius
10 x overall diameter

CONSTRUCTION

Conductor

Data Pair: Class 2 Stranded tinned copper - 24/19AWG (0.25mm²)

Power Pair: Class 2 Stranded tinned copper - 22/19AWG (0.35mm²)

Insulation

Pair 1 - Data: Foam-skin PE (Polyethylene)

Pair 2 - Power: Solid PE (Polyethylene)

Shield

AL/PET (Aluminium/Polyester Tape)

Drain Wire

Tinned copper - 24AWG

Overall Shield

TCWB (Tinned Copper Wire Braid)

Sheath

FRNC-LSZH (Flame Retardant Non Corrosive - Low Smoke Zero Halogen)

Core Identification

Pair 1: ○ White ● Blue

Pair 2: ● Black ● Red

Sheath Colour

● Violet

BSI KITEMARK[™] TESTED



KM 662609

Cables are tested and verified by The Cable Lab[®] to confirm they meet the quality standards required of the BSI Cable Batch Verification Kitemark[™]

STANDARDS

Flame Retardant according to BS EN/IEC 60332-1
Low Smoke Density / Halogen free according to IEC 61034-2, IEC 60754-1



UK LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab[®], a UKAS accredited ISO 17025 cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU, RoHS compliance has been tested and confirmed by The Cable Lab[®] as meeting the requirements of the BSI RoHS Trusted Kitemark[™].



DIMENSIONS

ELAND PART NO.	NOMINAL CROSS SECTIONAL AREA OF DATA PAIR CONDUCTOR mm ²	NOMINAL CROSS SECTIONAL AREA OF POWER SUPPLY PAIR CONDUCTOR mm ²	NOMINAL COVERAGE METALLIC BRAID	NOMINAL DIAMETER OF OUTER SHEATH mm	NOMINAL WEIGHT kg/km
VBUDNT04G5LSV10	0.25	0.35	65%	6.9	70

ELECTRICAL CHARACTERISTICS AT 20°C

DC CONDUCTOR RESISTANCE Ω/km		CAPACITANCE AT 800 HZ DATA PAIR nF/km	IMPEDANCE ≥ 1 MHz DATA PAIR Ω	ATTENUATION DATA PAIR dB/100m			DIELECTRIC STRENGTH kVac / 1 min	MINIMUM INSULATION RESISTANCE GΩxkm	TRANSFER IMPEDANCE AT 10 MHz mΩ/m
Data	Power Supply Pair			AT 125 kHz	AT 500 kHz	AT 1 MHz			
77	52	40	120	0.9	1.6	2.1	1.5	5.0	7

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.