

# 6491X / H07V-R / H07V-U / BS EN 50525-2-31 Cable



Eland Product Group: **A2X**

## APPLICATION

6491X Cable H07V-R/H07V-U is suitable for power and lighting circuits and building wiring. The cable is intended for use in semi-flush exposed conduits and embedded conduits as well as in closed installation ducts, and is ideal for the internal wiring of appliances.

## CONSTRUCTION

### Conductor

H07V-R: Class 2 stranded copper conductor to BS EN 60228 (previously BS 6360)

H07V-U: Class 1 solid copper conductor to BS EN 60228 (previously BS 6360)

### Insulation

PVC (Polyvinyl Chloride) Type T11 according to BS EN 50363

## CABLE STANDARDS

BS EN 50525-2-31 (previously BS 6004) BASEC approved, BS EN/IEC 60332-1-2



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

## CHARACTERISTICS

### Voltage Rating (U<sub>0</sub>/U)

450/750V

### Temperature Rating

-15°C to +70°C

### Minimum Bending Radius

Up to 10mm<sup>2</sup>: 3 x overall diameter

10mm<sup>2</sup> to 25mm<sup>2</sup>: 4 x overall diameter

Above 25mm<sup>2</sup>: 5 x overall diameter

### Insulation Colour

● Red ● Black ● Blue ● Yellow ○ White  
● Green/Yellow ● Grey ● Brown

## DIMENSIONS

ELAND PART NO.	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	NOMINAL THICKNESS OF INSULATION mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A2X*0015	1.5	0.7	2.9	22
A2X*0025	2.5	0.8	3.6	32
A2X*0040	4	0.8	4.1	50
A2X*0060	6	0.8	4.7	71
A2X*010	10	1	5.9	110
A2X*016	16	1	6.8	164
A2X*025	25	1.2	8.4	256
A2X*035	35	1.2	9.4	346
A2X*050	50	1.4	11	473
A2X*070	70	1.4	12.7	674
A2X*095	95	1.6	14.7	913
A2X*120	120	1.6	16.2	1150
A2X*150	150	1.8	18	1416
A2X*185	185	2	20	1749
A2X*240	240	2.2	23	2317
A2X*300	300	2.4	25.2	3049
A2X*400	400	2.6	28.4	3657
A2X*500	500	2.8	31.8	4700
A2X*630	630	2.8	38.1	5890

\*Eland Part No. shown above designate the sheath colour (\*). For each colour substitute \* for a colour code as listed below. e.g. A2XRD0040 = 4mm<sup>2</sup> Red

## Colour Codes

COLOUR	Black	Blue	Grey	Green/Yellow	Red	Yellow	Brown	White
CODE	BK	BL	GR	GY	RD	YW	BR	WH

## CONDUCTORS

### Class 2 Stranded Conductors for Single Core and Multi-Core Cables

NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	MINIMUM NO. OF WIRES IN CONDUCTOR						MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C
	Circular		Circular Compacted		Shaped		Annealed Copper Conductor
	Cu	Al	Cu	Al	Cu	Al	Plain Wires ohms/km
1.5	7	-	6	-	-	-	12.1
2.5	7	-	6	-	-	-	7.41
4	7	-	6	-	-	-	4.61
6	7	-	6	-	-	-	3.08
10	7	7	6	6	-	-	1.83
16	7	7	6	6	-	-	1.15
25	7	7	6	6	6	6	0.727
35	7	7	6	6	6	6	0.524
50	19	19	6	6	6	6	0.387
70	19	19	12	12	12	12	0.268
95	19	19	15	15	15	15	0.193
120	37	37	18	15	18	15	0.153
150	37	37	18	15	18	15	0.124
185	37	37	30	30	30	30	0.0991
240	37	37	34	30	34	30	0.0754
300	61	61	34	30	34	30	0.0601
400	61	61	53	53	53	53	0.047
500	61	61	53	53	53	53	0.0366
630	91	91	53	53	53	53	0.0283

The above table is in accordance with BS EN 60228 (previously BS 6360)

## ELECTRICAL CHARACTERISTICS

## Current Carrying Capacity

NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	REFERENCE METHOD A (ENCLOSED IN CONDUIT IN THERMALLY INSULATING WALL ETC) Amps		REFERENCE METHOD B (ENCLOSED IN CONDUIT ON A WALL OR IN A TRUNKING ETC) Amps		REFERENCE METHOD C (CLIPPED DIRECT) Amps		REFERENCE METHOD F (IN FREE AIR OR ON A PERFORATED CABLE TRAY ETC HORIZONTAL OR VERTICAL ETC) Amps				
							Touching			Spaced by one diameter	
										2 Cables Single-Phase AC or DC or 3 Cables Three-Phase AC flat	
2 Cables Single-Phase AC or DC	3 or 4 Cables Three-Phase AC	2 Cables Single-Phase AC or DC	3 or 4 Cables Three-Phase AC	2 Cables Single-Phase AC or DC flat or touching	3 or 4 Cables Three-Phase AC flat and touching or trefoil	2 Cables Single-Phase AC or DC flat	3 Cables Three-Phase AC flat	3 Cables Three-Phase AC trefoil			
1.5	14.5	13.5	17.5	15.5	20	18	-	-	-	-	-
2.5	20	18	24	21	27	25	-	-	-	-	-
4	26	24	32	28	37	33	-	-	-	-	-
6	34	31	41	36	47	43	-	-	-	-	-
10	46	42	57	50	65	59	-	-	-	-	-
16	61	56	76	68	87	79	-	-	-	-	-
25	80	73	101	89	114	104	131	114	110	146	130
35	99	89	125	110	141	129	162	143	137	181	162
50	119	108	151	134	182	167	196	174	167	219	197
70	151	136	192	171	234	214	251	225	216	281	254
95	182	164	232	207	284	261	304	275	264	341	311
120	210	188	269	239	330	303	352	321	308	396	362
150	240	216	300	262	381	349	406	372	356	456	419
185	273	245	341	296	436	400	463	427	409	521	480
240	321	286	400	346	515	472	546	507	485	615	569
300	367	328	458	394	594	545	629	587	561	709	659
400	-	-	546	467	694	634	754	689	656	852	795
500	-	-	626	533	792	723	868	789	749	982	920
630	-	-	720	611	904	826	1005	905	855	1138	1070

Ambient temperature: 30°C

Conductor operating temperature: 70°C

The above table is in accordance with Table 4D1A of the 17th Edition of IEE Wiring Regulations.

## Voltage Drop

NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	2 CABLES DC mV/A/m	2 CABLES SINGLE-PHASE AC mV/A/m									3 OR 4 CABLES THREE-PHASE AC mV/A/m											
		Reference Methods A and B (enclosed in conduit or trunking)			Reference Methods C, F (clipped direct, on tray or in free air)			Reference Methods A and B (enclosed in conduit or trunking)			Reference Methods C, F (clipped direct, on tray or in free air)											
					Cable Touching	Cable Spaced					Cable Touching Trefoil	Cable Touching Flat	Cable Spaced* Flat									
1.5	28	29			29	29		25			25	25	25									
2.5	18	18			18	18		15			15	15	15									
4	11	11			11	11		9.5			9.5	9.5	9.5									
6	7.3	7.3			7.3	7.3		6.4			6.4	6.4	6.4									
10	4.4	4.4			4.4	4.4		3.8			3.8	3.8	3.8									
16	2.8	2.8			2.8	2.8		2.4			2.4	2.4	2.4									
		r	x	z	r	x	z	r	x	z	r	x	z	r	x	z	r	x	z	r	x	z
25	1.75	1.80	0.33	1.80	1.75	0.20	1.75	1.75	0.29	1.80	1.50	0.29	1.55	1.50	0.18	1.50	0.15	0.25	1.55	1.50	0.32	1.55
35	1.25	1.30	0.31	1.30	1.25	0.20	1.25	1.25	0.28	1.30	1.10	0.27	1.10	1.10	0.17	1.10	0.10	0.24	1.10	1.10	0.32	1.15
50	0.93	0.95	0.30	1.00	0.93	0.19	0.95	0.93	0.28	0.97	0.81	0.26	0.85	0.80	0.17	0.82	0.80	0.24	0.84	0.80	0.32	0.86
70	0.63	0.65	0.29	0.72	0.63	0.19	0.66	0.63	0.27	0.69	0.56	0.25	0.61	0.55	0.16	0.57	0.55	0.24	0.60	0.55	0.31	0.63
95	0.46	0.49	0.28	0.56	0.47	0.18	0.50	0.47	0.27	0.54	0.42	0.24	0.48	0.41	0.16	0.43	0.41	0.23	0.47	0.40	0.31	0.51
120	0.36	0.39	0.27	0.47	0.37	0.18	0.41	0.37	0.26	0.45	0.33	0.23	0.41	0.32	0.15	0.36	0.32	0.23	0.40	0.32	0.30	0.44
150	0.29	0.31	0.27	0.41	0.30	0.18	0.34	0.29	0.26	0.39	0.27	0.23	0.36	0.26	0.15	0.30	0.26	0.23	0.34	0.26	0.30	0.40
185	0.23	0.25	0.27	0.37	0.24	0.17	0.29	0.24	0.26	0.35	0.22	0.23	0.32	0.21	0.15	0.26	0.21	0.22	0.31	0.21	0.30	0.36
240	0.18	0.20	0.26	0.33	0.19	0.17	0.25	0.19	0.25	0.31	0.17	0.23	0.29	0.16	0.15	0.22	0.16	0.22	0.27	0.16	0.29	0.34
300	0.15	0.16	0.26	0.31	0.15	0.17	0.22	0.15	0.25	0.29	0.14	0.23	0.27	0.13	0.14	0.19	0.13	0.22	0.25	0.13	0.29	0.32
400	0.11	0.13	0.26	0.29	0.12	0.16	0.20	0.12	0.25	0.27	0.12	0.22	0.25	0.11	0.14	0.18	0.11	0.21	0.24	0.10	0.29	0.31
500	0.086	0.11	0.26	0.28	0.98	0.155	0.185	0.093	0.24	0.26	0.10	0.22	0.25	0.086	0.135	0.16	0.086	0.21	0.23	0.081	0.29	0.30
630	0.068	0.094	0.25	0.27	0.081	0.155	0.175	0.076	0.24	0.25	0.08	0.22	0.24	0.072	0.135	0.15	0.072	0.21	0.22	0.066	0.28	0.29

Conductor operating temperature: 70°C

r = Resistive Component  
 x = Reactive Component  
 z = Impedance Value

\*Spacings larger than one cable diameter will result in a larger voltage drop.

The above table is in accordance with Table 4D1B of the 17th Edition of IEE Wiring Regulations.

For cables having conductors of 16mm<sup>2</sup> or less cross sectional area their inductances can be ignored and (mV/A/m)r values only are tabulated. For cables having conductors greater than 16mm<sup>2</sup>, cross sectional area the impedance values are given as (mV/A/m)z, together with the resistive component (mV/A/m)r and the reactive component (mV/A/m)x.

The above paragraph is extracted from Appendix 4 of the 17th Edition of IEE Wiring Regulations.

## DE-RATING FACTORS

For Ambient Air Temperatures other than 30°C

AMBIENT TEMPERATURE	25°C	30°C	35°C	40°C	45°C	50°C	55°C
DE-RATING FACTOR	1.03	1.00	0.94	0.87	0.79	0.71	0.61