



Belden 8778 Multi-Pair Cable



Eland Product Group: A4B

APPLICATION

Belden 8778 Multi-Pair Cables are used to connect multiple audio channels in low-level (microphone) and high-level (line) componentry such as console board equipment for recording studios, radio television stations, post-production facilities, and sound system installations.

CHARACTERISTICS

Voltage Rating
300V

Temperature Rating
-20°C to +80°C

Minimum Bending Radius
10 x overall diameter

CONSTRUCTION

Conductor
Class 2 stranded tinned copper

Insulation
PP (Polypropylene)

Screen
Beldfoil[®] (Aluminium foil polyester tape)

Drain Wire
Tinned copper

Sheath
PVC (Polyvinyl Chloride)

Core Identification
 Pair 1: ● Black ● Red
 Pair 2: ● Black ○ White
 Pair 3: ● Black ● Green
 Pair 4: ● Black ● Blue
 Pair 5: ● Black ● Yellow
 Pair 6: ● Black ● Brown

Sheath Colour
● Grey

STANDARDS

Belden 8778

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU, the RoHS Directive 2015/863/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

ELAND PART NO.	BELDEN REFERENCE	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS		NOMINAL OVERALL DIAMETER		NOMINAL WEIGHT	
				mm	in.	mm	in.	kg/km	mm
A4B8778	8778	6	AWG22(7)	0.03	0.762	0.352	8.94	70	104

PERFORMANCE CHARACTERISTICS

BELDEN REFERENCE	CAPACITANCE (CONDUCTOR TO CONDUCTOR)		CAPACITANCE (CONDUCTOR TO SHIELD)		NOMINAL INDUCTANCE	
	pF/ft.	pF/m	pF/ft.	pF/m	μH/ft.	μH/m
8778	30	98.4	55	180.4	0.18	0.59

ELECTRICAL CHARACTERISTICS

BELDEN REFERENCE	IMPEDANCE ohms	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C		NOMINAL VELOCITY OF PROPAGATION %	CURRENT CARRYING CAPACITY AT 25°C Amps
		ohms/1000ft.	ohms/km		
8778	50	15	49.2	66	2

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.