



LFH Rail Connection T0504 Cable (London Underground)



APPLICATION

A single core cable suitable for DC traction indication circuits and rail connection circuits.

CHARACTERISTICS

Voltage Rating
3kV

Temperature Rating
-15°C to +85°C

Minimum Bending Radius
6 x overall diameter

CONSTRUCTION

Conductor
Class 2 stranded Tinned copper conductor

Insulation
LFH (Limited Fire Hazard)

Sheath
LFH (Low Fire Hazard)

Sheath Colour
● Black with ● Yellow stripe

CABLE THIRD-PARTY ACCREDITATION



London Underground Limited (LUL) certified and listed on the Approved Products Register as meeting the requirements for installation within their network

STANDARDS

T0504, LUL

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NO. OF STRANDS	NOMINAL DIAMETER OF STRANDS mm	MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C ohms/km	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
T05041X4	4	0.5	7	0.85	4.7	21.6	624

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.