



Belden 9402 Multi-Conductor Audio, Control and Instrumentation Cable



Eland Product Group: **A4B**

APPLICATION

An individual screened multi-pair cable suitable for use in audio, monitoring and instrumentation applications.

CHARACTERISTICS

Voltage Rating
300V

Temperature Rating
-20°C to +80°C

Minimum Bending Radius
10 x overall diameter

CONSTRUCTION

Conductor
Class 2 stranded tinned copper conductor

Insulation
SR - PVC (Semi Rigid - Polyvinyl Chloride)

Screen
Beldfoil® (Aluminium foil polyester tape)

Drain Wire
Tinned copper

Sheath
PVC (Polyvinyl Chloride)

Pair Identification
Pair 1: ● Red ● Black
Pair 2: ● Green ○ White

Sheath Colour
● Grey

STANDARDS

UL1685-FT4, UL 2464

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable is compliant with European Regulation EN 50575, the Construction Products Regulation.



This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab[®] as meeting the requirements of the BSI RoHS Trusted Kitemark[™].





DIMENSIONS

ELAND PART NO.	BELDEN REFERENCE	NO. OF PAIRS	AWG (NO. OF STRANDS)	NOMINAL DIAMETER OF STRANDS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
A4B9402	9402	2	AWG20(7)	0.0810	7.62	72.92

ELECTRICAL CHARACTERISTICS

AWG (NO. OF STRANDS)	CAPACITANCE		INDUCTANCE $\mu\text{H}/\text{m}$	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
	Conductor to Conductor pF/m	Conductor to Shield pF/m		
AWG20(7)	180.455	311.695	0.558	30.5133