

Copper Tube Pin Terminals



Eland Product Group: FCA

APPLICATION

This range of pin terminals is designed to terminate conductors into contact blocks. The internal diameters suit standard cables as defined in BS EN 60228.

STANDARDS

BS EN 60228

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DIMENSIONS

ELAND PART NO.	CABLE SIZE mm ²	TOTAL LENGTH mm	PIN LENGTH mm	ENTRY WIDTH mm	PIN WIDTH mm	TOTAL WIDTH mm	PACK QUANTITY
FTP15	1.5	12.5	8	1.8	1.7	3.8	100
FTP25	2.5	12.5	8	2.4	1.7	4.4	100
FTP6	6	15.8	10	3.6	3.6	5.6	100
FTP10	10	24.1	13.2	4.8	4.3	6.8	100
FTP16	16	34.3	18.2	6	5.3	8	100
FTP25	25	38	18.5	7	7	9	100
FTP35	35	43.4	18.8	8.2	7	10.2	100
FTP50	50	50.5	19.2	9.5	8.4	12	100
FTP70	70	55	23	11.2	11	14.2	50
FTP95	95	55	23	13.4	12.5	16.4	50

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.