

FCRC Copper and Aluminium Cable Cutter



Eland Product Group: **FCA**

APPLICATION

For a clean cut with no flatterring of the cable.

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



DESCRIPTION

One Handed Ratchet Cutter with Replaceable Blades for Cutting Copper and Aluminium Cables

ELAND PART NO.	CABLE SIZE mm ²
FCCTG1	2.4 - 4.8

For Core Cutting of Copper and Aluminium Power Cables and Sector Cables

ELAND PART NO.	SIZE - POWER CABLES mm ²	SIZE - SECTOR CABLES mm ²
FCRC2	up to 325	up to 32

For Core Cutting of Copper and Aluminium Power Cables and Sector Cables

ELAND PART NO.	SIZE - POWER CABLES mm ²	SIZE - SECTOR CABLES mm ²
FCRC3	up to 400	up to 50

For Core Cutting of Copper and Aluminium Power Cables and Sector Cables

ELAND PART NO.	SIZE - POWER CABLES mm ²	SIZE - SECTOR CABLES mm ²
FCRC4	up to 400	up to 52

For Wire Armoured Cable (non-hardened steel)

ELAND PART NO.	CABLE SIZE mm ²
FCRC5	up to 80

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.