

Scame IP66/IP67 Plug



Eland Product Group: **SCA**

APPLICATION

IPP66/67 plugs for fixed or temporary use, where ingress protection is required.

CONSTRUCTION

Material

Halogen free engineering plastic

STANDARDS

BS EN 60309-1, BS EN 60309-2



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the Eland Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved product drawings. Conformance to RoHS (Restriction of the use of Hazardous Substances) is determined and confirmed.

CHARACTERISTICS

Voltage Rating

100/480V

Operating Temperature

-25°C to +40°C

Maximum Operating Temperature

+60°C

DIMENSIONS

ELAND PART NO.	POLES	AMPS	TYPE	VOLTAGE RATING V	COLOUR
SP-66SCYW/16A	2P+E	16	Screw	100 - 130	Yellow
SP-66SCYT/16A	2P+E	16	Screw	100 - 130	Yellow/Transparent
SP-66SCBL/16A	2P+E	16	Screw	200 - 250	Blue
SP-66SCBK/16A	2P+E	16	Screw	200 - 250	Black
SP-66SCBT/16A	2P+E	16	Screw	200 - 250	Blue/Transparent
SP-66SCRD/16A	2P+E	16	Screw	380 - 415	Red
SP-66IPYW/16A	2P+E	16	Insulation Perforating	100 - 130	Yellow
SP-66IPYT/16A	2P+E	16	Insulation Perforating	100 - 130	Yellow/Transparent
SP-66IPBL/16A	2P+E	16	Insulation Perforating	200 - 250	Blue
SP-66IPBK/16A	2P+E	16	Insulation Perforating	200 - 250	Black
SP-66IPBT/16A	2P+E	16	Insulation Perforating	200 - 250	Blue/Transparent
SP-66IPRD/16A	2P+E	16	Insulation Perforating	380 - 415	Red
SP-66SCYW/32A	2P+E	32	Screw	100 - 130	Yellow
SP-66SCBL/32A	2P+E	32	Screw	200 - 250	Blue
SP-66SCBK/32A	2P+E	32	Screw	200 - 250	Black
SP-66SCRD/32A	2P+E	32	Screw	380 - 415	Red
SP-66SCYW/63A	2P+E	63	Screw	100 - 130	Yellow
SP-66SCBL/63A	2P+E	63	Screw	200 - 250	Blue
SP-66SCRD/63A	2P+E	63	Screw	380 - 415	Red
SP-66SCYW/125A	2P+E	125	Screw	100 - 130	Yellow
SP-66SCBL/125A	2P+E	125	Screw	200 - 250	Blue
SP-66SCRD/125A	2P+E	125	Screw	380 - 415	Red
SP3-66SCBL/16A	3P+E	16	Screw	200 - 250	Blue
SP3-66SCRD/16A	3P+E	16	Screw	380 - 415	Red
SP3-66SCBK/16A	3P+E	16	Screw	380 - 415	Black
SP3-66IPBL/16A	3P+E	16	Insulation Perforating	200 - 250	Blue
SP3-66IPRD/16A	3P+E	16	Insulation Perforating	380 - 415	Red
SP3-66IPBK/16A	3P+E	16	Insulation Perforating	380 - 415	Black
SP3-66SCBL/32A	3P+E	32	Screw	200 - 250	Blue
SP3-66SCRD/32A	3P+E	32	Screw	380 - 415	Red
SP3-66SCBK/32A	3P+E	32	Screw	380 - 415	Black
SP3-66SCRD/32A	3P+E	32	Screw	380 - 440	Red
SP3-66SCBL/63A	3P+E	63	Screw	200 - 250	Blue
SP3-66SCRD/63A	3P+E	63	Screw	380 - 415	Red
SP3-66SCBL/125A	3P+E	125	Screw	200 - 250	Blue
SP3-66SCRD/125A	3P+E	125	Screw	380 - 415	Red
SP4-66SCRD/16A	3P+N+E	16	Screw	346 - 415	Red
SP4-66SCBK/16A	3P+N+E	16	Screw	346 - 415	Black
SP4-66IPRD/16A	3P+N+E	16	Insulation Perforating	346 - 415	Red
SP4-66IPBK/16A	3P+N+E	16	Insulation Perforating	346 - 415	Black
SP4-66SCRD/32A	3P+N+E	32	Screw	346 - 415	Red
SP4-66SCBK/32A	3P+N+E	32	Screw	346 - 415	Black
SP4-66SCRD/63A	3P+N+E	63	Screw	346 - 415	Red
SP4-66SCRD/125A	3P+N+E	125	Screw	346 - 415	Red