



NEK 606 RFOU(i) 250V S101 Cable



Eland Product Group: ASH

APPLICATION

A flame-retardant and halogen-free individually screened instrumentation cable designed for fixed installation in conditions where oil and gas rigs are usually working. Suitable for use in extreme temperatures, saline atmospheres, and where UV radiation, hydrocarbons, oils and drilling fluids and muds are present, meeting the requirements of NEK606.

CHARACTERISTICS

Voltage Rating U_0/U
150/250V

Maximum Operating Voltage U_{max}
300V

Temperature Range
+90°C

Minimum Bending Radius
4 x overall diameter

CONSTRUCTION

Conductor

Class 2 tinned annealed copper conductor

Insulation

EPR (Ethylene Propylene Rubber) Halogen free compound

Individual Screen

Copper polyester tape + tinned copper drain wire

Inner Sheath

SHF2 extruded compound

Armour

TCWB (Tinned Copper Wire Braid)

Sheath

SHF2 H-M compound

Core Identification

Pair: ● Black ● Light Blue

Triple: ● Black ● Light Blue ● Brown

Multi pairs/triples: Progressively numbered

Sheath Colour

● Blue ● Grey

CABLE THIRD-PARTY ACCREDITATIONS

We supply DNV approved products

Cables are tested and certified by Det Norske Veritas (Norway)

We supply Lloyds Register approved products

Cables are tested and certified by Lloyds Register (UK)

We supply ABS approved products

Cables are tested and certified by American Bureau of Shipping (USA)

STANDARDS

NEK 606, IEC 60092-376, IEC 60092-360

Flame Retardancy IEC 60332-1-2 IEC 60332-3-22 CAT A

Corrosivity IEC 60754-1 /2 IEC 60684-2

Smoke Density IEC 61034-1 /2

UV Resistance UL 1581 § 1200

Ozone Resistance IEC 60092.360

Mineral/Hydraulic Oils & Mud Resistance NEK 606

Impact & Cold Resistance CSA C 22.2 N° 0.3-09 & N° 38-18

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECEE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].





DIMENSIONS

ELAND PART NO.	NO. OF PAIRS/TRIPLES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER UNDER ARMOUR mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
ASHNRI0175**	1P	0.75	7.0	10.9	190
ASHNRI0110**	1P	1.0	7.6	11.5	215
ASHNRI0115**	1P	1.5	8.3	12.2	245
ASHNRI0125**	1P	2.5	9.1	13.0	290
ASHNRI1T75**	1T	0.75	7.4	11.2	210
ASHNRI1T10**	1T	1.0	8.0	11.9	235
ASHNRI1T15**	1T	1.5	8.8	12.6	275
ASHNRI1T25**	1T	2.5	9.7	13.7	330
ASHNRI0275**	2P	0.75	11.1	15.7	405
ASHNRI0210**	2P	1.0	12.1	16.8	470
ASHNRI0215**	2P	1.5	13.3	18.1	545
ASHNRI0225**	2P	2.5	14.8	20.3	655
ASHNRI2T75**	2T	0.75	12.1	16.9	475
ASHNRI2T10**	2T	1.0	13.2	18.0	540
ASHNRI2T15**	2T	1.5	14.6	20.1	640
ASHNRI3T75**	3T	0.75	12.8	17.5	535
ASHNRI3T10**	3T	1.0	14.0	18.7	610
ASHNRI3T15**	3T	1.5	15.5	21.0	735
ASHNRI0475**	4P	0.75	12.8	17.6	545
ASHNRI0410**	4P	1.0	14.0	18.8	620
ASHNRI0415**	4P	1.5	15.5	21.3	750
ASHNRI0425**	4P	2.5	17.2	23.0	910
ASHNRI4T75**	4T	0.75	14.0	19.0	630
ASHNRI4T10**	4T	1.0	15.4	21.1	740
ASHNRI4T15**	4T	1.5	17.0	22.8	885
ASHNRI4T25**	4T	2.5	19.0	24.8	1080
ASHNRI0775**	7P	0.75	15.3	21.1	765
ASHNRI0710**	7P	1.0	16.8	22.7	895
ASHNRI0715**	7P	1.5	18.6	24.6	1060
ASHNRI7T75**	7T	0.75	17.5	23.4	945
ASHNRI7T10**	7T	1.0	19.2	25.4	1105
ASHNRI7T15**	7T	1.5	21.4	27.6	1340
ASHNRI0875**	8P	0.75	16.3	22.2	860
ASHNRI0810**	8P	1.0	17.9	24.0	1000
ASHNRI0815**	8P	1.5	19.9	26.3	1205
ASHNRI0825**	8P	2.5	22.2	28.6	1485
ASHNRI8T75**	8T	0.75	18.7	24.9	1070
ASHNRI8T10**	8T	1.0	20.6	27.0	1250
ASHNRI8T15**	8T	1.5	22.9	29.3	1520
ASHNRI8T25**	8T	2.5	26.1	32.5	1940
ASHNRI1275**	12P	0.75	18.8	24.4	1130
ASHNRI1210**	12P	1.0	21.4	27.8	1365
ASHNRI1215**	12P	1.5	24.2	30.8	1700
ASHNRI1225**	12P	2.5	27.0	33.6	2110

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.

ELAND PART NO.	NO. OF PAIRS/TRIPLES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL DIAMETER UNDER ARMOUR mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
ASHNRI12T75**	12T	0.75	21.9	28.5	1440
ASHNRI12T10**	12T	1.0	24.6	31.2	1720
ASHNRI12T15**	12T	1.5	27.4	34.4	2145
ASHNRI16T75**	16P	0.75	22.4	29.0	1505
ASHNRI16T10**	16P	1.0	24.7	31.3	1765
ASHNRI16T15**	16P	1.5	27.5	34.5	2160
ASHNRI16T75**	16T	0.75	25.3	32.1	1860
ASHNRI16T10**	16T	1.0	27.9	34.9	2185
ASHNRI16T15**	16T	1.5	31.1	38.9	2800
ASHNRI19T75**	19P	0.75	24.1	30.9	1740
ASHNRI19T10**	19P	1.0	26.6	33.4	2030
ASHNRI19T15**	19P	1.5	29.7	36.7	2470
ASHNRI19T75**	19T	0.75	27.3	34.3	2140
ASHNRI19T10**	19T	1.0	30.1	38.1	2625
ASHNRI19T15**	19T	1.5	33.6	41.6	3230
ASHNRI24T75**	24P	0.75	26.7	33.7	2100
ASHNRI24T10**	24P	1.0	29.5	37.0	2500
ASHNRI24T15**	24P	1.5	33.3	41.5	3180
ASHNRI24T75**	24T	0.75	30.3	38.2	2700
ASHNRI24T10**	24T	1.0	33.9	42.0	3220
ASHNRI24T15**	24T	1.5	37.8	46.4	4025
ASHNRI32T75**	32P	0.75	30.4	38.3	2760
ASHNRI32T10**	32P	1.0	34.0	42.1	3305
ASHNRI32T15**	32P	1.5	38.0	46.3	4025
ASHNRI32T75**	32T	0.75	34.9	43.2	3475
ASHNRI32T10**	32T	1.0	36.8	47.1	4100
ASHNRI32T15**	32T	1.5	43.1	51.9	5115

P = Pairs

T = Triples

Eland Part No. shown above designate the gland colour (). For each colour substitute * for a colour code as listed below. e.g. ASHNRI0175GR = 0.75mm² Grey

COLOUR CODES

COLOUR	Grey	Blue
CODE	GR	BL

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.



ELECTRICAL CHARACTERISTICS - PAIRS

NOMINAL CROSS SECTIONAL AREA mm ²	MAX. CONDUCTOR RESISTANCE Ω/km		REACTANCE Ω/km		MAX. CAPACITANCE μF/Km	NOMINAL INDUCTANCE μH/Km	IMPEDANCE @ 50 & 60 HZ Ω/km		MAX. L/R RATIO @ 1KHZ μH/Ω
	20°C	90°C	50 HZ	60 HZ			20°C	90°C	
0.75	26.3	33.5	0.106	0.127	0.09	336	26.3	33.5	12.8
1.0	19.3	24.6	0.098	0.118	0.095	312	19.3	24.6	16.2
1.5	12.9	16.5	0.099	0.118	0.1	314	12.9	16.5	24.3

ELECTRICAL CHARACTERISTICS - TRIPLES

NOMINAL CROSS SECTIONAL AREA mm ²	MAX. CONDUCTOR RESISTANCE Ω/km		REACTANCE Ω/km		MAX. CAPACITANCE μF/Km	NOMINAL INDUCTANCE μH/Km	IMPEDANCE @ 50 & 60 HZ Ω/km		MAX. L/R RATIO @ 1KHZ μH/Ω
	20°C	90°C	50 HZ	60 HZ			20°C	90°C	
0.75	26	33.5	0.106	0.127	0.09	336	26.3	33.5	12.8
1.0	19.3	24.6	0.098	0.118	0.095	312	19.3	24.6	16.2
1.5	12.9	16.5	0.099	0.118	0.1	314	12.9	16.5	24.3

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.