


Resin Straight Joint Kits



APPLICATION

Designed to enable core cross-over and can be used with both compression splices or mechanical core connectors, available as separate items. Range of LV straight joints with transparent 2-part polyurethane resin mixing system which ensures safe handling.

Suitable for EPR, XLPE, PVC or LZSH sheath types. Lead and PILC cables require additional earthing. Suitable for wire armour, waveform or braided armour cables

CONSTRUCTION

Braid

Armour continuity braid

Tape

Mastic tape

STANDARDS

BS EN 50393

THE CABLE LAB[®]

AN ISO/IEC 17025 AND IECCE CBTL ACCREDITED FACILITY

Our world-class testing facility assures the quality and compliance of this cable through a continuous and rigorous testing regime.



SUSTAINABILITY COMMITMENT

We are on a journey to Net Zero.

We've committed to near-term emissions reductions and a net-zero target with the Science Based Targets initiative and we're a signatory to the United Nations Global Compact Sustainable Development Goals.

Learn more about embodied carbon and our carbon emissions reduction actions, our comprehensive recycling services, and wider ESG activities for sustainable operations at: www.elandcables.com/company/about-us/esg-sustainability



REGULATORY COMPLIANCE

This cable meets the requirements of the RoHS Directive 2015/65/EU and Reach Directive EC 1907/2006. RoHS compliance has been tested and confirmed by The Cable Lab[®].



ELAND PART NO.	MAXIMUM DIAMETER	EXTERNAL LENGTH	EXTERNAL WIDTH	SINGLE CORE XLPE/AWA/LSF	TWO CORE XLPE/AWA/LSF	THREE CORE XLPE/AWA/LSF	FOUR CORE XLPE/AWA/LSF
S6	27	195	45	-	1.5-10mm ²	1.5-6.0mm ²	1.5-6.0mm ²
S10	33	210	61	25-50mm ²	16mm ²	10mm ²	10mm ²
S16	39	226	71	50-70mm ²	25mm ²	16mm ²	16mm ²
S25	39	256	71	70-95mm ²	35mm ²	25mm ²	25mm ²
S35	39	325	80	120-185mm ²	50mm ²	35-50mm ²	35mm ²
S50	48	400	90	240-400mm ²	70mm ²	70mm ²	50mm ²
S95	45	575	165	400-630mm ²	95-120mm ²	95mm ²	70-95mm ²
S120	53	630	190	800-1000mm ²	150-185mm ²	120-150mm ²	120mm ²
S185	62	735	210	-	240-300mm ²	185mm ²	150-185mm ²
S300	73	885	235	-	400mm ²	240-400mm ²	240-300mm ²
S400	80	960	295	-	-	-	400mm ²

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.